



DIAMETER AIR PASSAGE	L	ATTENUATION AT 250 HZ	
Ø mm	mm	dB(A)	A
80	500	9,5	64,82
100	500	8	70,69
125	500	6,5	82,07
140	500	5,5	87,92
150	500	5	90,41
160	500	5	91,65
180	500	4,5	111,55
200	500	4,5	113,33
224	500	4,5	135,70
250	500	4	149,21
280	500	3,5	166,08
300	500	3	173,35
315	500	3	178,17
355	500	3	221,34
400	500	2,5	266,97
80	1000	19	100,17
100	1000	16	115,28
125	1000	13	130,91
140	1000	11	151,51
150	1000	10	151,51
160	1000	10	151,51
180	1000	9	184,89
200	1000	9	184,89
224	1000	9	218,83
250	1000	8	218,83
280	1000	7	252,22
300	1000	6	252,22
315	1000	6	257,75
355	1000	6	285,97
400	1000	5	312,62
80	1500	28,5	125,23
100	1500	24	141,39
125	1500	19,5	160,41
140	1500	16,5	178,51
150	1500	15	181,35
160	1500	15	182,06
180	1500	13,5	213,15
200	1500	13,5	224,52
224	1500	13,5	263,24
250	1500	12	285,97
280	1500	10,5	341,75
300	1500	9	350,44
315	1500	9	351,52
355	1500	9	422,58
400	1500	7,5	503,39
80	2000	39	161,81
100	2000	32	185,61
125	2000	26	196,64
140	2000	22	229,14
150	2000	20	232,87
160	2000	20	233,91
180	2000	18	269,10
200	2000	18	287,21
224	2000	18	332,68
250	2000	16	358,98
280	2000	14	429,50
300	2000	12	439,26
315	2000	12	498,78
355	2000	12	565,37
400	2000	10	657,74

CHARACTERISTICS:
Flexible circular sound attenuators, insulation 50 mm.

CONSTRUCTION:
External sheet of aluminium with mineral wool insulation and inner sheet of aluminium. Not flammable in accordance with DIN 4102 class A1, resistant to 200 ° C, bending radius equal to 3 diameters.

FIXING:
Coupling.

DISIGNI - DRAWINGS

